$STRIDE^{^{TM}}$



Stride shown with Pearl shell



Stride shown with Pearl shell / Teak cabinet and Polymer step



Seating Capacity	3 adults
Dimensions	7' x 5'5" x 29"/ 2.13m x 1.65m x 0.74m
Water Capacity	215 gallons/825 liters
Weight	635 lbs./290 kg dry; 2955 lbs./1355 kg filled*
Spa Shell Options	Pearl, Sterling Marble, Tuscan Sun or Desert
Cabinet Options	Coastal Gray, Espresso, Teak
Jets - 18 (all with stainless steel trim)	3 Directional Hydromassage jets 1 Rotary Hydromassage jets 14 Directional Precision [™] jets
Jet Pump	Wavemaster 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque
Water Care System	FROG® In-Line Cartridge Ready
Ozone System (Optional)	FreshWater® III Corona Discharge
Control System	IQ 2020° 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz
Lighting	6 multi-color LED points of light, dimmable
Heater	No-Fault® 1000w/115v
Energy Efficiency	FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Effective Filtration Area	30 sq. ft., top loading
Vinyl Cover	3.5" to 2.5" tapered, 2 lb. density foam core Ash, Caramel or Chestnut
Cover Lifter (Optional)	CoverCradle®, CoverCradle II, Lift 'n Glide® or UpRite®
Steps (Optional)	Everwood® or Polymer Coastal Gray, Espresso or Teak

- Includes water and 3 adults weighing 175 lbs. each.
 Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.
 G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode.
 Export models available in 230v, 50Hz, 1000w heater.

From the makers of

