

TX



TX shown with Pearl shell



TX shown with Pearl shell and Espresso cabinet

| | |
|------------------------------------|---|
| Seating Capacity | 2 adults |
| Dimensions | 5'8.5" x 5'8.5" x 29"/1.74m x 1.74m x .74m |
| Water Capacity | 140 gallons/525 liters |
| Weight | 525 lbs./240 kg dry; 2,045 lbs./925 kg filled* |
| Spa Shell Options | Pearl or Desert |
| Cabinet Options | Coastal Gray, Espresso or Teak |
| Jets - 10 | 1 Moto-Massage® jet 1 Rotary Hydromassage jet 8 Directional Precision® jets |
| Waterfall | n/a |
| Jet Pump 1 | Wavemaster® 4200; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque |
| Jet Pump 2 | n/a |
| Circulation Pump (Optional) | SilentFlo 5000® |
| Water Care System | FROG® In-Line Cartridge Ready |
| Ozone System (Optional) | FreshWater® III Corona Discharge |
| Control System | IQ 2020® 115v/15 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz |
| Lighting | Blue LED light, dimmable; Splendors® multi-colored LED light, dimmable (optional) |
| Heater | No-Fault® 1000w/115v |
| Energy Efficiency | FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law |
| Effective Filtration Area | 30 sq. ft., top loading |
| Vinyl Cover | 3" to 2" tapered, 1 lb. density foam core Ash, Caramel or Chestnut |
| Cover Lifter (Optional) | n/a |
| Steps (Optional) | Everwood® or Polymer Coastal Gray, Espresso or Teak |

* Includes water and 2 adults weighing 175 lbs. each.

** Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

*** G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode.
Export models available in 230v, 50Hz, 1000w heater.

From the makers of

